




| Part numbers for RO-series | RO-Compact 1 | RO-Compact 2 | RO-Compact 3 |
|--|---|--|---|
| |  |  |  |
| System with Integrated Bypass | 170151 | 170152 | 170153 |
| System with No-Bypass | 170151-U | 170152-U | 170153-U |
| Minimum Rated Hourly Production@ 15 °C Litres/hour | 160 | 300 | 420 |
| Minimum Daily Production¹ Litres/day | 3840 | 7200 | 10080 |
| Reservoir Volume Litres | 35 | 66 | 66 |
| Recovery Time of Reservoir Minutes | 14 | 14 | 10 |
| Recovery (Hard Water Feed) Max. 10`dh | 50% | 50% | 50% |
| Recovery (Hard Water Feed) Max. 25`dh | 40% | - | - |
| Recovery (Soft Water Feed) | 75% | 75% | 75% |
| Delivery Flow Rate Litres/hour | 1250 | 1250 | 1250 |
| Delivery Pressure bar | 3,5 | 3,5 | 3,5 |
| Membrane Type | Compact low3-4021 | Compact low3-4021 | Compact low3-4021 |
| Number of Membranes | 1 | 2 | 3 |
| Sound Pressure Level² db | 61 | 62 | 61 |

¹Based on feed TDS of 500 mg/l and a water temperature of 15 °C.

²Sound measured 1 m from the front of the unit and 1,6 m from the floor with the lid on.